

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**





(11) Publication number:

**0 041 373
A1**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 81902360.0

(51) Int. Cl. 2: C 12 N 13/00

(22) Date of filing: 29.05.81

(30) Priority: 30.05.80 (US) 154706
21.02.81 US 235471

(31) Date of publication of application:
09.12.81 Bulletin 81/49

(32) Designated Contracting States:
BE CH DE FR GB IT LI NL SE

(71) Applicant: RPG INDUSTRIES, INC.
One Gateway Center
Pittsburgh Pennsylvania 15772(US)

(72) Inventor: Carlin, William Worth
116 Fulton Place
Portland Texas 78874(US)

(73) Representative: Shipton, Gordon Owen et al,
W.P. THOMPSON & CO. Coopers Building Church Street
Liverpool L1 3AB(GB)

(54) Electrostimulation of microbial reactions.

(57) A method of fermenting a substrate with a microorganism by forming a broth comprising the substrate and the microorganism, and forming a fermentation product therefrom characterised in that a fermentation stimulating electrical signal is imposed across the broth.

EP 0 041 373 A1

H 1581/P
0041373

1.

DESCRIPTION"ELECTROSTIMULATION OF MICROBIAL REACTIONS"

Microbe reactions, i.e., fermentation, are the biological conversion of a feedstock, i.e., a substrate, to a metabolite, i.e., a product, by the actions of microbes. Microbe reactions are characterized by the growth of the microbe, and the subsequent formation of a metabolite product. That is, substrate is used initially for the growth and maintenance of the microbes, and subsequently for both the growth and maintenance of the microbes and for the formation of product. Product formation is related to the concentration of substrate, the concentration of microbes, and the yield coefficients of product and microbes with respect to the substrate. Moreover, the concentration of microbes is a function of the specific growth rate of the microbes, and the yield coefficient of the microbes with respect to the substrate.

Fermentation reactions are typically slow reactions. That is, they require long residence time, i.e., high ratios of reaction medium volume per unit volume of production per unit time. They also have a long initiation time. That is, metabolite product cannot be formed in large quantities until high concentrations of microbe are present. Nutrient, i.e., substrate, is initially utilized primarily to grow and maintain microbes, and there-after it is utilized to a greater extent to form metabolite product.

Moreover, the reactions, involving microbial growth and division, are complex. For example, when the microbes are bacteria, cell growth and division is by fission, i.e., an individual cell will double in mass and content of cell constituents, and then split into two identical daughter cells. By way of contrast, yeasts are a class of microorganism that grow and divide by budding. That is, a bud will grow on an individual cell

0041373

2.

until it matches the size of the original cell, and then separate, leaving a bud scar. Fungi grow by chain elongation and branching, i.e., with growth proceeding from the tip of the mycelium through the formation of
5 septa between individual cells. Cell division may require anywhere from 15 minutes to an hour for bacterial growth, from 45 minutes to 2 hours for yeast growth, and from one to eight hours for fungi or mycelial growth.

10 The specific path of product synthesis, i.e., the reaction path for the formation of the metabolite product from the substrate or nutrient is not clearly understood for every fermentation reaction. However, it is believed to depend upon microbe growth and
15 concentration, nutrient utilization, and metabolic controls.

It has now been found that the reaction rate of fermentation reactions, that is, the yield per unit time, unit volume, unit nutrient or substrate concentration, and unit microbe concentration is enhanced by the
20 application of an alternating or pulsed high frequency electric field to the reaction medium of microbes, substrate, and nutrients.

As used herein, the terms "fermentation", "fermentation reactions", and "reactions utilising
25 fermentation techniques" include aerobic and anaerobic metabolic activity of a microbe or microbes in which chemical changes are brought about in an organic or inorganic substrate, and any process mediated by or involving microbes or microorganisms in which a product
30 accrues.

As used herein, the terms "microbes", "microbe", "microorganisms", and "micro-organism" include prokaryotes and eukaryotes. "Prokaryotes", as used herein, means
35 unicellular microorganisms, including bacteria and unicellular blue-green algae. "Eukaryotes", as used

0041373

3.

herein, means multi-cellular microorganisms, including fungi, yeasts and actinomyces. As used herein, the terms "microbes", "microbe", "microorganisms" and "micro-organism" include immobilized microbes and systems and structures of immobilized microbes as well as non-immobilized microbes. As used herein, the terms "microbes", "microbe", "microorganisms", and "microorganism" include both naturally occurring strains and artificial recombinant strains.

5 Fermentation reactions, i.e., fungus, yeast, actinomyces, and bacterial fermentation reactions are utilized industrially. Fermentation reactions are capable of wider industrial use based upon raw material availability and costs, by-product usage, and increased reaction rates.

15 According to the invention described herein, any or all of the reaction rate, the inoculum build up, or efficiency of conversion are increased by electrical stimulation. Electrical stimulation may be utilized to reduce the time required to carry out the reaction or to increase the productivity of a given unit of production, that is to increase the number of batches that can be fermented in a given reaction vessel.

20 By electrical stimulation is meant the application of a pulsed or alternating high frequency electric signal field across the broth whereby to pass an electrical current through the broth, e.g., by inserting electrodes in the broth, under conditions which increase the rate of the microbial reaction, while substantially avoiding significant destruction of the micro-organisms, e.g., fungi, bacteria, yeasts or actinomycetes, the reactants, e.g., the substrate, or the products.

30 It has been found that a frequency of from about 1 kilohertz to about 1000 kilohertz is particularly satisfactory in carrying out the method of this invention.

0041373

4.

The electrical stimulation electrical current may be an alternating current or pulsed direct current. It should have a frequency of from about 1 kilohertz to about 1000 kilohertz, although frequencies below about 10 megahertz may be used as well as frequencies above about 0.1 kilohertz with some increases in yield. However, care should be taken e.g. by using a frequency above about 0.1 kilohertz, to avoid large amounts of electrolysis occurring within the reaction medium at low frequencies.

The method of this invention may advantageously be carried out at various ranges of the electrolytic variables, i.e., electrode area, inter-electrode spacing, inter-electrode volume, current, current density, current per unit inter-electrode volume, current per unit broth volume, voltage, voltage per unit inter-electrode spacing, power per unit inter-electrode volume, power per unit broth volume, and frequency.

For example, the method of this invention has been carried out utilizing Saccharomyces cerevisiae to ferment glucose at currents per unit interelectrode volume of from about 1×10^{-3} milliamperes per cubic centimeter to about 30×10^{-3} milliamperes per cubic centimeter of inter-electrode volume, at currents per unit broth volume of from about 1×10^{-4} milliamperes per cubic centimeter to about 50×10^{-4} milliamperes per cubic centimeter of broth, current densities of about 2×10^{-2} milliamperes per square centimeter to 5×10^{-1} milliamperes per square centimeter of electrode area, voltage fluxes of 0.1 to 3 millivolts per centimeter of inter-electrode space, interelectrode power dissipations of 0.2×10^{-7} watts per cubic centimeter to 6×10^{-7} watts per cubic centimeter of interelectrode volume and broth power dissipations of 0.2×10^{-8} watts per cubic centimeter of broth volume to 8×10^{-8} watts per cubic

0041373

5.

centimeter of broth volume. Electrolytic variables, i.e. currents, voltages, and power dissipations, and products and quotients thereof, outside the above ranges may be utilized as long as care is taken, by avoiding simultaneous astomer of the ranges, to avoid destruction of the microbes.

According to one exemplification of the method herein contemplated, a reaction medium of a hexose, e.g., glucose, other nutrients, and a yeast, Saccharomyces cerevisiae is provided. A pair of electrodes are spaced about 4 to about 7 centimeters from each other within the broth, and an electrical current at a current density of about 0.1 to about 0.3 milliamperes per square centimeter of electrode area is passed through the reaction medium at a frequency of about 100 kilohertz to about 1000 kilohertz. In this way, the yield of product per unit of substrate per unit time is increased by about 15 to about 20 percent compound with the result without electrical stimulation.

According to an alternative exemplification of the method of this invention, a reaction broth of a bacterium such as Bacillus polymyxa or Bacillus licheniformis, and glucose are prepared. The fermentation reaction is then carried out while an alternating current having a frequency of about 1 kilohertz to about 1000 kilohertz, an imposed voltage signal sufficient to provide a current of 1×10^{-3} milliamperes per cubic centimeters of interelectrode volume and 10^{-1} to 5 milliamperes per liter of solution is imposed across the broth. The resulting production rate of butane diol is increased by about 20 percent compared with the result without electrical stimulation.

The method of electrostimulated fermentation herein described is useful with single cell blue-green algae, bacteria, yeasts, and actinomycetes. Suitable yeasts are for example, baker's yeast and brewer's yeast, i.e.,

0041373

6.

single cell yeast of the Saccharomycoidaceae group, as exemplified by Saccharomyces cerevisiae.

- The method of electrostimulated fermentation is useful with various feedstocks. Exemplary are various
- 5 carbohydrate substrates. By carbohydrates we mean for example polyhydroxy aldehydes, polyhydroxy ketones, and substances that yield polyhydroxy aldehydes or polyhydroxy ketones upon hydrolysis or saccharification. Exemplary carbohydrates are sugars, i.e. saccharides.
- 10 The saccharides useful in the method of this invention may be monosaccharides, i.e., carbohydrates incapable of further hydrolysis, or polysaccharides, i.e. carbohydrates that yield monosaccharides upon hydrolysis or saccharification. Naturally occurring saccharides useful as
- 15 substrates in the methods of this invention include heptoses, hexoses, pentoses, tetroses, triose, homopolysaccharides thereof, and heteropolysaccharides thereof. Exemplary hexoses include glucose, fructose, mannose, galactose, and the fructose-glucose disaccharide, sucrose.
- 20 Exemplary pentoses include arabinose, xylose, ribose, and apiose. Exemplary polysaccharides include sucrose, mentioned above, maltose, lactose, raffinose, starch, glycogen, cellulose, pectins, chitin, inulin, agar, hemicelluloses, plant gums and mucilages, and immuno-
- 25 polysaccharides. By carbohydrates we also mean sugar alcohols, e.g. sorbitol, mannitol, galactitol, or the inositols. Industrial sources of carbohydrate include by way of exemplification manure, cellulosic wastes, molasses, whey, sugar, grain starches, and byproduct
- 30 carbohydrates. Suitable grain starches include by way of exemplification corn, corn stover, wheat, barley, straw, and bagasse.

- Amino acids may be utilized as substrates for fermentation type reactions. They may be recovered as
- 35 products of fermentation type reactions, or they may be

0041373

7.

intermediates, produced in one fermentation type reaction as a substrate for a subsequent fermentation type reaction. Exemplary alpha-amino acids include glycine, alanine, valine, leucine, isoleucine, serine, threonine, cysteine, cystine, methionine, phenylalanine, tyrosine, proline, tryptophan, lysine, arginine, histidine, aspartic acid, and glutamic acid. The above enumeration is intended to be exemplary and not exclusionary.

Other substrates which may be utilized are, for example, hydrocarbons, e.g., aliphatic hydrocarbons, carbocyclic hydrocarbons, and heterocyclic hydrocarbons. As used herein, hydrocarbons include substituted hydrocarbons, e.g. halogenated hydrocarbons, and hydrocarbons having one or more functional groups, e.g. alcohol, ketone, aldehyde, acid, ether, amine, amidine, N-alkyl amide, N,N-dialkyl amide, imidic ester, imide, aldimine, ketimine, thiol, thio ether, disulfide, thio acid, dithioacid, thio aldehyde, thio ketone, sulfonium, sulfoxide, sulfinic acid, sulfone, sulfonic acid, phosphite, phosphine, phosphonate, phosphate, orthocarbonate, carbonate, chloroformate, carbamate, carbamide (including urea), N-alkylurea, o-alkylurea, cyanate, isocyanate, carbodiimide, xanthate, thiocarbamate, thiocyanate, isothiocyanate, diazoate, or diazocyanide groups. In many cases the substrate is a dilute pollutant, and is degraded or metabolized to a non-polluting product.

The method of electrostimulated fermentation may be utilized with both aerobic and anaerobic fermentations.

Electrostimulated fermentation is useful in the industrial scale production of any product that can be produced by fermentation techniques, as described hereinabove. These products include the following, which enumeration is exemplary and not exclusionary: antibiotics; organic solvents, for example alcohols, e.g., butanol, ethanol, and amyl alcohols, ketones e.g. acetone;

0041373

8.

gases, e.g. carbon dioxide and hydrogen; beverages, e.g. wines, beers and liquors; foods, e.g. cheeses, fermented milks, pickles, sauerkraut, soy sauce, yeast, vinegar, and mushrooms; flavoring agents e.g. monosodium glutamate; 5 organic acids and hydroxy acids e.g. lactic acid, acetic acid, citric acid, gluconic acid, butyric acid, fumaric acid, and itaconic acid; glycerol; amino acids, e.g. L-glutamic acid and L-lysine; steroids; organic transformations, including steroid, alkaloid, and antibiotic 10 transformations; yeasts, including food yeasts and animal feed yeasts, legume inoculants; pesticides, e.g. microbial and bacterial pesticides; vitamins and growth stimulants, e.g. vitamin B 12 vitamin A, riboflavin and gibberalkines; enzymes including amylases, proteolytic 15 enzymes, pectinases, invertases, and cellulases, inter alia; fats; fatty acids; alcohols; fuels; and hydrocarbons.

The electrostimulation method herein contemplated may also be used for the control or destruction of 20 deleterious substances, e.g., pollutants, and aqueous dispersions, suspensions and solutions of hydrocarbons or halocarbons, including polymers thereof.

While the electrostimulate fermentation method described herein above is useful with various microbes 25 in various fermentation reactions, the method of this invention may be exemplified by the Weizmann Process for the bacterial fermentation of starch to yield n-butyl alcohol, ethyl alcohol, and acetone; the production of ethyl alcohol by the use of Rhizopus formosaensis, 30 Saccharomyces cerevisiae, Saccharomyces uvarum, or Aspergillus foetidus; the production of acetic acid utilizing Acetobacteri alcoholophilus, Lactobacillus plantarum, or Polyperus palustris; the production of acetone utilizing Clostridium; the production of butanol 35 utilizing Clostridium; the production of glycerol

0041373

9.

utilizing Bacillus licheniformis or Saccharomyces rouxii;
the production of acetic acid using Acetobacteri pasteur-
ianus; the production of wines using Saccharomyces
chevalieri, Saccharomyces ocrvisiae, Saccharomyces roei,
5 Saccharomyces vafar, Saccharomyces vini, Torulaspore
florentina, Saccharomyces aceti, or Saccharomyces oxidans;
the production of edible proteins utilizing C. lactomium
cellulolyticum, Geotrichum candidum, Candida utilis,
Cellulomonas or Alcaligenes faecalis; the production of
10 anthraquinones utilizing Chrysosporium merdarium,
Helminthosporium cynadonitis, or Penicillium islandicum;
the production of antibiotics utilizing Byssoschlamys
nivea, Fusarium equiseti, Gliocladium, Aspergillus astierus,
Aspergillus sulphureus, Penicillium cyclopium, Penicillium
15 martensii, Penicillium palitans, Penicillium puberulum,
Aspergillus nidulans, Penicillium chrysogenum, Penicillium
notatum, acromonium strictum, Cephalosporium chrysogenum,
Serratia rebindaea, Streptomyces lavendulae, Streptomyces
clausigii, Streptomyces lipmanii, Acinetobacter calco-
20 aceticus, Bacillus cereus, Bacillus licheniformis, or
Bacillus subtilis; the production of L-arginine by
Bacillus subtilis, Breribacterium florum, Corynebacterium
glutamicum, or Protaminobacter thiaminophagus; the
production of ascorbic acid by Escherichia; the production
25 of biotin by Corynebacterium primorioxidans, or Pseudo-
monas putabilis; the production of butanediols using
Bacillus licheniformis, Bacillus polymyxa, or Klebsiella
pneumoniae; the production of butyric acid using Buty-
rivibrio fibrisolvens; the production of caprylic acid
30 using Ranibacterium alactolyticum; the production of
carboxylic acid utilizing Sacchromycopsis lipolytica, or
Sporolomyces odorus; the production of formic acid using
Polyporus palustris; the production of fructose utilizing
Bacillus megaterium, Pseudomonas boreopolis or Pseudomonas
35 fluorescens; the production of gluconic acid using

0041373

10.

- Aspergillus carbonarius, or Penicillium chrysogenum; the production of glucose utilizing Trichoderma longibrachiatum; the production of p-hydroxy benzaldehyde using Saccharomyces satic; the production of single cell
- 5 proteins utilizing Arthrobacter petroleophagus, Arthrobacter rubellus, Arthrobacter, Aspergillus fumigatus, Cellulomonas cartelyticum, Corynebacterium fujiokense, Kluyuromyces fragilis morehella crassipe, Mycobacterium cureatum, Mycobacterium petroleophilum, or
- 10 Nocardia neoopaca, and the production of xanthan gum using, e.g., Xanthamonas campestris. The method of electrostimulated fermentation may be used in the fermentation of substrates to obtain vitamins, antibiotics, and enzymes.
- 15 Electrostimulated fermentation also finds utility in microbial cellulose digestion, e.g., with Polyangium cellulorum; cleaning metallic surfaces, e.g., with Thiobacillus ferrooxidans or Thiobacillus thiooxidans; degradation of cellulose; degradation of cyanides in
- 20 waste water, e.g., with Bacillus subtilis, Corynebacterium, or Nocardia rubropertincta; degradation of ethylene glycol with unidentified bacterium, ATCC 27042; degradation of chlorinated phenol fungicides; degradation of systemic fungicides, e.g., with Rhizopus japonicus; degradation
- 25 of hydrocarbons, e.g., with Aspergillus versicolor, Brettanomyces petrophilum, Candida petrophilum, Candida tropicalis, Cladosporium resinae, Cunninghamella elegans, Eupenicillium zonatum, Saccharomycaroris lipolytica, or Torulopsis petrophilum; degradation of jet fuel,
- 30 e.g., with Acremonium strictum, Alternaria alternata, Aspergillus fumigatus, or Cladosporium resinae; degradation of methanol, e.g., with Hansenula polymorpha; degradation of nitriles in waste water, e.g., with
- 35 Alcaligenes visolactis, Nocardia rubropuncta, or Bacillus subtilis; degradation of petroleum, e.g. with Aspergillus surcoacidium, Candida parapsilosis, Candida

0041373

11.

- tropicalis, Candida utilis, Cladosporium cladosporioides, Myrothecium verrucaria, Nocardia corallina, Nocardia globerula, Nocardia opain, Nocardia paraffinae, Nocardia rubra, Penicillium, Prototheca, Rhodotorula, Saccharomyces cerevisiae, or Saccharomycopsis lipolytica; the degradation of phenol, e.g., with Gloeoporus dichrous, or Rhodotorula glutinis; the degradation of wood; phosphate removal in sewage treatment, e.g., with Chrysosporium pannorum, Geotrichum candidum, Mucor hiemalis, and Faecilomyces carneus; water pollution control, e.g., with Rhodotorula glutinis and Trichothecium roseum; and the production of dextrans by the fermentation of sucrose, e.g., with Leuconostoc mesenteroides and Betacoccus arabino sareus; and the production of immunopolysaccharides.

The following examples are illustrative:

EXAMPLE I

Electrostimulated and conventional fermentations were carried out in a batch reactor.

- The reaction broth was prepared by placing 1500 milliliters of distilled water in a sterilized 3 liter beaker. Carbohydrates, water and nutrients were added to the beaker in the following quantities:

Glucose	220 grams
NaCl	3 grams
$(\text{NH}_4)_2\text{SO}_4$	6 grams
K_2HPO_4	2.4 grams
KH_2PO_4	0.4 grams

Distilled Water to make 2 liters

- Whereafter, a 200 milliliter portion of the glucose solution was placed in a sterilized container and 14 grams of Fleischmann's Baker's Yeast, Saccharomyces cerevisiae, was added thereto and stirred to form a slurry. The yeast-glucose slurry was divided into two equal

0041373

12.

portions of 100 milliliters each and put into two 1 liter sterilized resin kettles. To each of the divided yeast-glucose slurries were added 2.1 grams of corn meal, and 700 milliliters of the glucose solution.

5 The outlets of both reactors were connected to wet test meters to measure the gas produced. One reactor was run without electrical stimulation.

The other reactor had an electrode pair of two 4 square inch stainless steel electrodes, 4 centimeters apart. A signal generator was utilized to generate a 10 300 kilohertz, sine wave, voltage signal. A 50 millivolt signal caused a current of 1.5 milliamperes to flow.

Eight simultaneous, side-by-side runs were made, with one reactor having electrical stimulation and the 15 other reactor being unstimulated.

The results shown in Table I, below, were obtained:

TABLE I

COMPARISON OF ELECTRO-STIMULATED FERMENTATION WITH CONVENTIONAL FERMENTATION

	<u>Length of Run (hours)</u>	<u>Current (milli- amperes)</u>	<u>Moles of Ethanol- Stimulated (gel chro- matographic)</u>	<u>Moles of Ethanol- Unstimulated (gel chro- matographic)</u>
20				
25	26.5	1.25	0.476	0.456
	19	1.25	0.506	0.475
	22	1.5	0.561	0.469
	47.5	1.5	0.967	0.930
	23.4	2.25	0.840	0.855
30	27	2.5	0.420	0.390
	43.4	1.5 -6.1	1.14	1.16
	25.5	2.25-6.5	0.713	0.707

EXAMPLE II

Electrostimulated fermentation was carried out in 35 a batch reactor to determine the effect of current and frequency.

0041373

13.

The reaction broth was prepared by placing one liter of distilled water in a sterilized beaker. Carbohydrates, water and nutrients were added to the beaker in the following quantities:

5	Sucrose	100 grams/liter
	NaCl	1.5 grams/liter
	$(\text{NH}_4)_2\text{SO}_4$	3.1 grams/liter
	K_2HPO_4	1.2 grams/liter
	KH_2PO_4	0.2 grams/liter

10 Distilled water

1.2 liters of the solution were placed in a 1.5 liter resin kettle.

15 Thereafter, 7.0 grams of Fleischmann's dried Baker's Yeast, *saccharomyces cerevisiae*, was poured on top of the reaction broth. The reactor was then closed, with gas venting through a water seal bubbler. The mixture was allowed to stand for 18 hours.

20 Thereafter, at 24 hour intervals, the slurry was removed from the reactor by aspiration and filtered to recover the yeast cake. The yeast cake was added to 1.0 liter of fresh reaction broth and returned to the kettle, which was sealed with a gas vent to a burette of 1 percent sulfuric acid and stirred for 5 minutes.

25 After two hours, four gas volume readings were taken at one half hour intervals, and used to calculate a base gas evolution rate, R_0 . Thereafter, electrical stimulation was commenced. Four gas volume readings were taken at half hour intervals beginning one hour after electrical stimulation, and used to calculate a test gas evolution rate, R_T . For the fermentation with electro-stimulation, R_T is the gas evolution rate. For the fermentation without electrostimulation, R_T is the gas evolution rate measured simultaneously with and calculated in the same way as the gas evolution rate for electro-stimulation. After three hours of electrical stimulation,

30

35

0041373

14.

the current was turned off for 19 hours, and then reaction slurry removed as described above.

Each electrode was a nickel wire, 0.63 millimeters diameter, spiraled twice around a four inch (10 cm) long, 3 millimeter diameter glass rod. The electrodes were spaced 6.5 to 7.0 centimeters apart. Voltage was provided by a Dynascan 3010 function generator.

The effect of applied electrical field was as shown in Table II below:

10

TABLE II

EFFECT OF APPLIED CURRENT (AT 100 KILOHERTZ)
ON GAS EVOLUTION

	Current (milli- amperes)	(R_T/R_0) (without current)	(R_T/R_0) (with current)	(R_T/R_0) with current $\frac{(R_T/R_0) \text{ with current}}{(R_T/R_0) \text{ without current}}$
15	0.15	1.05	1.15	1.10
	0.15	0.92	1.02	1.11
	1.5	1.01	1.13	1.12
20	1.5	0.98	1.17	1.19

The effect of frequency was as shown in Table III below:

TABLE III

EFFECT OF FREQUENCY (AT 0.15 MILLIAMPERES)
ON GAS EVOLUTION

25

	Frequency (kilohertz)	(R_T/R_0) (without current)	(R_T/R_0) (with current)	(R_T/R_0) with current $\frac{(R_T/R_0) \text{ with current}}{(R_T/R_0) \text{ without current}}$
30	10	0.83	0.92	1.11
	100	1.05	1.15	1.10
	100	0.92	1.02	1.11

EXAMPLE III

Fermentation of glucose with S.cervisiae was carried out with and without electrical stimulation.

35

0041373

15.

A broth was prepared containing 220 grams of glucose, 7.5 grams of *S.cerevisae*, 10 grams of NH_4Cl , 22 grams of $\text{Na}_2\text{HPO}_4 \times 7 \text{ H}_2\text{O}$, 12 grams of KH_2PO_4 , 1 gram of MgSO_4 , and 0.04 grams of CaCl_2 , and distilled water to make two liters.

The broth was divided into two portions and placed in sterilized resin kettles. Both kettles were stirred continuously with a magnetic stirrer. One kettle, intended for electrostimulation, had an electrode pair, each electrode was a 0.63 millimeter diameter nickel wire spiraled twice around a four inch (10 cm) long, 3 millimeter diameter, glass rod. The electrodes were spaced 6.5 to 7.0 millimeters apart.

The fermentation was carried out at 30 degrees Centigrade for 23.5 hours. A signal generator was utilized to generate a 300 kilohertz, 50 millivolt, sine wave signal. The results shown below were obtained:

S.CERVISIAE FERMENTATION
OF GLUCOSE

	WITHOUT ELECTRICAL STIMULATION	WITH ELECTRICAL STIMULATION
FREQUENCY	---	300 kilohertz
CURRENT	---	1.5 milliamperes
25 INITIAL YEAST (GRAMS/ LITER)	3.4	6.5
FINAL YEAST (GRAMS/ LITER)	8.8	9.3
30 INITIAL GLUCOSE (GRAMS/ LITER)	108.9	106.3
FINAL GLUCOSE (GRAMS/ LITER)	4.3	<0.20
INITIAL ALCOHOL (GRAMS/LITER)	0.7	0.8
FINAL ALCOHOL (GRAMS/LITER)	43.0	54.4
35 GRAMS OF YEAST/GRAMS OF GLUCOSE-HOUR	2.18×10^{-3}	2.83×10^{-3}
GRAMS OF ALCOHOL/GRAMS OF GLUCOSE-HOUR	1.71×10^{-2}	2.18×10^{-2}
40 GRAMS OF ALCOHOL/GRAMS OF YEAST (FINAL)	4.87	5.72

0041373

16.

CETT. COUNT OF 200 SQUARES (three pipette samples per kettle)

	SAMPLE 1	660	865
	SAMPLE 2	739	895
5	SAMPLE 3	632	804
	MEAN	677	855
	RANGE	107	91
	STANDARD DEVIATION	63	53
10	PERCENT RELATIVE STANDARD DEVIATION	9.3	6.2
	DIFFERENCE IN MEANS	178	
	$\sqrt{\frac{\sigma_1^2}{n_1} + \frac{\sigma_2^2}{n_2}} =$	47	
15	(61 is the stranded deviation and n_1 is the number of replications).	26 ± 7% RELATIVE (at 1 standard deviation level)	

The student's "t" test was applied to the cell counts. A qt of 3.79 with a probability of 0.02 was obtained. That is, the probability that random errors would result in the 26% relative difference observed was less than 2 percent.

EXAMPLE IV

A series of tests were conducted to compare electrostimulated fermentation with conventional fermentation. For each test a simple nutrient solution was prepared. A portion of the nutrient solution was withdrawn to make a yeast solution. The remainder of the nutrient solution was divided into two equal portions and placed into two identical laboratory fermenters. Both fermenters had an electrode pair. Fleischmann's Baker's Yeast, Saccharomyces cerevisiae, was slurried in the remainder of the single nutrient solution. The nutrient solution, containing the yeast, was divided in half. Each half was placed into one of the two identical laboratory fermenters. A voltage

0041373

17.

signal was applied across one solution only of the pair. Solution samples were simultaneously taken from both solutions of the pair. Differences between the two fermentations of a pair were attributed to electro-
5 stimulation, while differences between sets of pairs of fermentations were attributed to conditions of the nutrient and inoculum solutions prior to commencing the tests.

For each fermentation a resin kettle fermenter was
10 used. The resin kettle fermenter had an inside diameter of 10 centimeters, a depth of 15 centimeters, and was sealed on top. Each resin kettle fermenter had a sample probe, a pH probe, a mechanical stirrer, a sodium hydroxide inlet, a gas outlet, and an electrode pair. The
15 electrodes were a pair of two inch (5 cm) by two inch (5 cm) stainless steel plate electrodes spaced two inches (5 cm) apart.

A glucose solution was prepared by adding in order:

	Glucose · H ₂ O	220 grams
20	NH ₄ Cl	10 grams
	Na ₂ HPO ₄ · 7H ₂ O	22 grams
	KH ₂ PO ₄	12 gram
	MgSO ₄	1 gram
	CaCl ₂	0.04 gram
25	H ₂ O	to make 2 liters

The glucose solution was boiled, and the pH was adjusted to pH--5 with H₃PO₄.

A yeast slurry was prepared by withdrawing 200 milliliters of the glucose solution, and stirring 3.6
30 grams of Fleischmann's Baker's Yeast Saccharomyces cerevisiae into the nutrient.

Each test was commenced by dividing the nutrient solution into two 300 milliliter portions and placing

0041373

18.

one portion of the nutrient solution into each resin kettle fermenter. Thereafter the slurry of yeast and nutrient was divided into two 100 milliliter portions. One portion of the yeast-nutrient slurry was added to each of the resin kettles.

The resin kettles were maintained at a temperature of 30 degrees Centigrade by immersion in a water bath. The pH was maintained between pH 4.7 and pH 5.2 by addition of aqueous NaOH. In each run a 300 kilohertz, 1.5 milliampere, 50 millivolt signal was applied across the electrode pair in one kettle. No signal was applied to the electrode pair in the other kettle.

The following results were obtained:

<u>Set 1</u>					
15	<u>ELAPSED TIME</u>	<u>NO CURRENT</u>		<u>CURRENT</u>	
		<u>Ethyl Alcohol (grms/liter)</u>	<u>Glucose (grms/liter)</u>	<u>Ethyl Alcohol (grms/liter)</u>	<u>Glucose (grms/liter)</u>
20	(hours)				
	1.25	1.17	98	.72	100
	3	1.87	96	1.96	98
	6	5.28	78	5.72	79
	25	31.8	<0.25	40.4	<0.25
25	Final Yeast (grms/liter)	2.54		2.63	

<u>Set 2</u>					
30	<u>ELAPSED TIME</u>	<u>NO CURRENT</u>		<u>CURRENT</u>	
		<u>Ethyl Alcohol (grms/liter)</u>	<u>Glucose (grms/liter)</u>	<u>Ethyl Alcohol (grms/liter)</u>	<u>Glucose (grms/liter)</u>
35	(hours)				
	1	0.09	98	0.09	103
	2	0.53	85	0.71	98
	4.5	2.7	78	2.2	76
	5.5	5.6	72	6.9	64
	28	40.2	<0.25	57.0	<0.25
40	Final Yeast (grms/liter)	0.466		0.504	

0041373

19.

Set 3ELAPSED
TIMENO CURRENTCURRENT

<u>(hours)</u>	<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>	<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>
1	3.0	87	3.5	88
3	8.5	87	11.0	70
4.5	22.9	40	28.0	45
6	37.9	19	37.0	19
22.5	44.2	<0.25	48.7	<0.25
Final Yeast (grms/liter)	9.0		9.8	

Set 4ELAPSED
TIMENO CURRENTCURRENT

<u>(hours)</u>	<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>	<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>
1	0.7	103	0.6	110
2	2.9	98	2.5	95
3	3.1	84	3.4	92
4	5.2	78	5.4	82
5	11.6	60	10.5	62
6	18.7	30.2	19.9	10.3
7	24.8	.3	27.1	.3
8	31.9	---	32.0	---
9	41.7	---	51.0	---
24	46.0	<0.25	56.0	<0.25
Final Yeast (grms/liter)	8.9		9.6	

0041373

20.

Set 5

5	<u>ELAPSED TIME</u> (hours)	<u>NO CURRENT</u>		<u>CURRENT</u>	
		<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>	<u>Ethyl Alcohol (grms/ liter)</u>	<u>Glucose (grms/ liter)</u>
	1	1.0	109	1.1	107
	2	2.0	90	2.8	97
10	3	4.9	81	5.1	83
	4	9.5	80	8.0	80
	5	17.0	70	17.3	69
	6	19.1	54	17.7	56
	7	21.7	35	24.0	39
15	8	32.4	21	37.1	27
	23.5	41.4	4	46.9	0.25
	Final Yeast (grms/liter)		9.9		10.5

While the invention has been described with respect
 20 to certain exemplifications and embodiments, that is
 with respect to certain microbes, i.e., bacteria,
 actinomycetes, fungi, and yeasts, certain substrates,
 i.e., hydrocarbons, and carbohydrates, and certain
 products, it is not to be so limited, except as in the
 25 claims appended hereto.

0041373

-21-

CLAIMS

1. A method of fermenting a substrate with a microorganism by forming a broth comprising the substrate and the microorganism, and forming a fermentation product therefrom characterised in that a fermentation stimulating electrical signal is imposed across the broth.
2. A method according to claim 1 characterised in that the microorganism is yeast, actinomycetes, bacteria, or unicellular blue-green algae.
3. A method according to claim 2 characterised in that the yeast is a Saccharomycoideae or a Saccharomyces cerevisiae.
4. A method according to claim 1, 2 or 3 characterised in that the substrate is a carbohydrate, hydrocarbon or amino acid.
5. A method according to claim 4 characterised in that the carbohydrate is glucose, fructose or mannose.
6. A method according to claim 4 characterised in that the carbohydrate is a polysaccharide.
7. A method according to any of claims 1 to 6 characterised in that the electrical signal is an alternating current signal or a pulsed direct current signal.
8. A method according to any of claims 1 to 7 characterised in that the electrical signal has a frequency of 0.1 kilohertz to 10 megahertz.
9. A method according to any of claims 1 to 7 wherein the electrical signal has a frequency of 1 kilohertz to 1000 kilohertz.
10. A method according to any of claims 1 to 9 characterised in that the current per unit of inter-electrode volume is from 1×10^{-3} to 30×10^3 milliamperes per cubic centimeter.
11. A method according to any of claims 1 to 10 characterised in that the current per unit of broth is

0041373

-22-

from 1×10^{-4} to 50×10^{-4} milliamperes per cubic centimeter.

12. A method according to any of claims 1 to 11 characterised in that the current density is from 2×10^{-2} to 50×10^{-2} milliamperes per square centimeters.

13. A method according to any of claims 1 to 12 characterised in that the voltage flux is 0.1 to 5 millivolts per centimeter.

14. A method according to any of claims 1 to 13 characterised in that the interelectrode power dissipation is from 0.2×10^{-7} to 6×10^{-7} watts per cubic centimeter of interelectrode volume.

15. A method according to any of claims 1 to 14 characterised in that the broth power dissipation is from 0.2×10^{-8} to 8×10^{-8} watts per cubic centimeter of broth.



European Patent
Office

EUROPEAN SEARCH REPORT

0041373

EP 01 30 2368 Application number

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int. Cl.)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
X	<p>AGRICULTURAL AND BIOLOGICAL CHEMISTRY, vol. 43, no. 10, October 1979, Tokyo, JP, M. HONGO and M. IWAHARA: "Application of electroenergizing method to L-glutamic acid fermentation", pages 2075-2081</p> <p>* The whole document, in particular the abstract and page 2076, paragraph 2 *</p>	1, 2, 4-5, 7, 12, 13	C 12 N 13/00
X	<p>CHEMICAL ABSTRACTS, vol. 85, no. 25, December 20, 1976, page 401, abstract 190704h Columbus, Ohio, USA I. KREPIS et al. "Increase in biomass growth and in the physiological and biochemical activity of baker's yeasts <i>Saccharomyces cerevisiae</i> using electrophysical agents"</p> <p>& ELEKTRON. OBRAB. MATER 1976 (4), 60-2</p> <p>* Abstract *</p>	1-5, 7	TECHNICAL FIELDS SEARCHED (Int. Cl.) C 12 N 13/00
X	<p>DE - A - 2 841 933 (KABEL UND METALLWERKE GUTENHOFFNUNGSHUTTE)</p> <p>* The whole document *</p>	1-2, 7	CATEGORY OF CITED DOCUMENTS
X	<p>DE - B - 2 052 548 (F.W. BRAUSS and A. VARGA)</p> <p>* The whole document *</p>	1-5, 7-12	<p>X: particularly relevant A: technological background U: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: conflicting application D: document cited in the application L: citation for other reasons</p>
X	<p>DE - C - 567 184 (F. SCHICK)</p>	1-5, 13	
<p>The present search report has been drawn up for all claims</p>			<p>&: member of the same patent family, corresponding document</p>
Place of search The Hague		Date of completion of the search 05-08-1981	Examiner GALLIGANI



European Patent
Office

EUROPEAN SEARCH REPORT

0041373

Application number

EP 81 30 2368

-2-

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int. Cl.)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
	* Whole document *		
	--		
X	DE - C - 572 960 (F. SCHICK) * The whole document *	1-5, 13	
	--		
X	CHEMICAL ABSTRACTS, vol. 77, no. 7, August 14, 1972, page 347, abstract 46742m Columbus, Ohio, USA & JP - A - 72 14745 (AJINOMOTO CO. INC) (10-05-1972) * Whole abstract *	1, 2, 4-5, 7, 13	TECHNICAL FIELDS SEARCHED (Int. Cl.)
	--		
X	CHEMICAL ABSTRACTS, vol. 75, no. 23, December 6, 1971, pages 211-212, abstract 139401y Columbus, Ohio, USA & JP - A - 71 27712 (AJINOMOTO CO. INC.) (11-08-1971) * Whole abstract *	1, 2, 4, 5, 7, 13	
	--		
X	FR - A - 1 057 842 (H. KLIEWE, G. NEIDL) * The whole document, in particular: page 1, paragraph 3; page 4, summary *	1, 2, 4, 5, 7-12	
	--		
X	DD - A - 74 753 (H. SCHROEDER) * The whole document *	1, 2, 4-7, 13	
	--		

European Patent
Office

EUROPEAN SEARCH REPORT

0041373

Application number

EP 81 30 2368

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (Int. Cl.)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
X	FR - A - 843 924 (J.R.E SANDSTROM) * Page 3, summary *	1-7	
			TECHNICAL FIELDS SEARCHED (Int. Cl.)